

Name:CBQY Explosion proof Fluorescent lamps



Application:

1. can be used in zone1.zand2,zand20,zand21,zand22 hazardous areas.
2. can be used in IIA,IIB,IIC group explosive atmosphere.
3. can be used in flammable dust areas

Feature:

1. the glass fiber strengthen unsaturated polyester mould pressing shape outer covering.have the strength high,bear the impact and the good function in etc.in corrosion.
2. poly carbonate transparent chimney.
3. the outer shell is for increasing the peaceful type construction,having the watertightness,dust palliative...etc.advantage.
4. the inside places the switch adoption flameproof a piece,be the product open can cut off the power supply automatially.
5. single footlights tube installed inside,starting with fast instantaneous.canrefit the one foot light tube according to the customer request.
6. the emergency device can be provided according according to user's request.
7. wiring by cable or steel pipe.

Main technical parameters:

Type	Tated volta ge	Ra te d po we r	Ca ble s out sid e dia	Ex-ma rk	Prote ction grade	Corrosion- proof
------	----------------------	--------------------------------	--	-------------	-------------------------	---------------------



Tel: 86-577-27866615 / E-mail: cxs@light-tower.cn <http://www.light-tower.cn>

				meter			
CBQY-2			2*				
*20	220v		20	10-	ExedII		
CBQY—	50hz		2*	14	CT5	IP65	WF2
2*40			40				

Emergency equipment parameters

Starting duration in emergency (s)	Charging time (h)	Light time in emergency (min)
0.3	24	90