

Name: CBD51 flame-proof explosion proof flood light



Application:

1. Can be used in Zone 1 and Zone 2 dangerous places.
2. Can be used in IIA, IIB groups explosive atmosphere.
3. suitable for incandescent lamp, mercury vapor, high-pressure sodium vapor lamp, metal halide lamp.

Notice: can be install lamp cover according to user's requitment

Features:

1. diecasted aluminum alloy shell with.
2. pressure-casted formation, compact structure and aesthetic appearance.
3. suspension type thumb nut is used for fastening so that it can be quickly opened up and downward is convenient for maintenance.
4. suitable for steel pipe.
5. suitable for GB3836-2000, IEC6007 standard request.

Main technical parameters:

Ex-mark	protection grade	cable' soutsidedia meter(mm)	inlet' sthe read (G")	lamp' sock' et	Mass(kg)
ExdIIBT4	IP54	10-14	3/4	E27	4.5

Supplied with lamps:

Lamp type	Self-ballasted mercury lamp	Incandescent lamp	Mercury vapor lamp	Hi-pressure so-diumlamp	Metal halide lamp
Rated	220V/50HZ				



Tel: 86-577-27866615 / E-mail: cxs@light-tower.cn <http://www.light-tower.cn>

voltage (v)					
Rated	125		80		70
power (w)	160	200	125	110	100