

Name: CQY6802 All-direction Truck Light Tower



Applicable Place:

Suitable for all kinds of indoor and outdoor worksite. Such as coal industry, petroleum and chemical industry, electric power, metallurgy, railway, iron and steel, shipping, army, aviation, police and fire-fighting, government and large-scale factory's fixed lighting need.

Functions:

Illumination performance: the lamp panel is composed of 2 highly effective Phillips tubes of 400W. According to the site requirement. Do adjust each cap up and down. Left and right and separately. Do adjust each cap up and down, left and right separately revolves to realize 360C Omni.

Illumination: also can install the cap equably in the panels to for directions illuminations. The whole illumination gives dual attention far and near. The higher the illumination brightness is, high and the scope is wide. Phillips tube has long service life.

Function performance: selects three expansionist and contraction air cylinder as the fluctuation adjustment way. The biggest height is 4.5 meters, and the light covering radius amounts 35-55 meters.

Working time: when use power set to supply power, full filling fuel oil one time may continuously work above 13 hours. Using 220V may supply long time illumination.

Convenient operation: may separately control each lamp's open and close through the wireless remote control within 50 meters. Use air pump or the manual air valve to control the fluctuation of flex pole.

Applicable place: the lamp plates, the cylinder and the generation set are the overall construction. The generator base is loaded with universal wheel and rail wheel, and can move on the pits road surface and the railway rail the whole uses the high quality imported metal material, with compact structure, stable performance, which guarantees normal work under each kind of adverse circumstance and the climatic conditions showing water-proof, spurning water proof, and the wind resistant grade is 8 levels.

Custom made capacity, in order to meet the customer demand, if our standard equipment can't satisfy for customers' working need, we can adjust the cap quantity, power, spotlight or floodlight. Raising eight of the flex pole and generating set according to you request.



Tel: 86-577-27866615 / E-mail: cxs@light-tower.cn <http://www.light-tower.cn>

Main Technical Parameter:

1. Rated voltage: AC220V/50Hz
2. Lamp plates:
 - (1) Cap power: 400W*2(halogen tungsten lamp)
 - (2) Cap luminous flux: Halogen tungsten lamp: 36000lm, Sodium: 48000lm
 - (3) Lamp bulb life: Halogen tungsten lamp: 8000lm, Sodium: 18000lm
3. working time: Full filling fuel oil one time: 13h
4. Flex pole: min height: 1800mm, Max height: 4500/6000mm
5. Generating set: rated output voltage: AC220V/50Hz, Power/as online tank capacity: 2000W/15L
6. Outline dimension: 800*500*2000mm, Lamp plate size: 400*380*300mm
7. Weight: 61kg