

Name: CQY3000B Working light



Applicable Place:

Suitable for all kinds of indoor and outdoor worksite. Such as coal industry, petroleum and chemical industry, electric power, metallurgy, railway, iron and steel, shipping, army, aviation, police and fire-fighting, government and large-scale factory's fixed lighting need.

Applicable Place:

1. Luminance: Lamp plate is made up of two 500W PHI LIPS Brand lamp heads. The lamp heads can illuminate in four different directions evenly according to the requirement of working sites each lamp head can be rotated upwards, downwards left and right to illuminate in angle of 360° Philips lamp head is high, lifetime of bulb is long.
2. illuminating Range: Adopting extension cylinder of 2 sections as lifting method maximum lifting height is 28m, Turn the lamp head upwards and downwards to adjust the illuminating. angle of beam radius of covering lighting can reach 35-55m Illuminating time: Connected with 220V main power, lamp of can work long time. it can be also connected with generator.
3. Applicability: Lower part of cylinder for lamp is installed with adjustable tripods, could use in various area. Have the good characteristic of small weight and consentient to carry and large using range
4. Custom-tailor Service: If the standard equipment of the lamp cannot meet the working requirement of clients, our company can regulates Lamp head quantity of Lamp plate power, flood lamp or spotlight, lifting height of extension cylinder and generator to meet the individual requirement of clients.

Main technical parameter:

1. Rated voltage: 220V
2. Lamp: Working voltage: 220V, Lamp head power: 2*500W, Lamp head luminous: 10000lm, Average using time: 10000h
3. working time, Main power: Long time
4. Extension cylinder, Min height: 1200mm, Max height: 2800mm, The largest height: 2800mm
- 5, Outsize (L*M*H) Lamp panel: 700*160*450mm
- 6, Weight: 8kg